



Product Information

20.02.2017

MARLIPAL O13/60

Composition

Oxoalcohol C 13 + 6 mol of ethylene oxide

INCI: Trideceth-6

Product data (specification)

Property	Value	Unit	Test method
Appearance at 20 °C	liquid, clear to turbid	-	visual
Iodine colour number	≤ 2	mg l/100 ml	DIN EN 1557
Cloud point (10 % in 25 % butyl diglycol solution)	69 - 72	°C	DIN EN 1890
pH (2 % in fully demin. water)	5 - 7	-	DIN EN 1262

General product description

Property	Value	Unit	Test method
Density at 50 °C	about 0.95	g/ml	DIN 51757
Refractive index n 50/D	about 1.448	-	DGF C - IV 5
Setting point	about + 3	°C	DIN ISO 3841
Flash point	> 150	°C	ASTM D 92
Ignition temperature	about 355	°C	DIN 51794
Polyethylene glycol	≤ 2.0	% by mass	HPLC
Water	≤ 0.5	% by mass	DIN EN 13267
Viscosity at 50 °C (Brookfield)	about 20	mPa s	DIN ISO 2555

Transport and packaging

Road tankers, about 950 kg containers, about 200 kg iron drums

Sasol Germany GmbH

Anckelmannsplatz 1, 20537 Hamburg Postanschrift: Postfach 26 18 05, 20508 Hamburg
Telefon: +49 40 63 684-1000 Telefax: +49 40 63 684-3700 info@de.sasol.com www.sasol.com
Geschäftsführung: Dr. Jens Straatmann Vorsitzender des Aufsichtsrats: Christian Schindler
Sitz der Gesellschaft: Hamburg Registergericht: Amtsgericht Hamburg HRB 78475



Product Information

20.02.2017

MARLIPAL O13/60

Storage

Stainless steel vessels (Steel No.: 1.4541 or 1.4571)

Handling instructions

The effects of extreme temperatures (cold, heat) may cause the product to become turbid, viscous, congeal or separate. In such cases mixing at normal temperatures (i.e. room temperature) will restore the product for use.

Data on material safety, as well as transport classes and on toxicology and biodegradability can be obtained from the material safety data sheet.

This information is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party patent rights. In particular, no guarantee of properties in the legal sense is implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Reference to trade names used by other companies is neither a recommendation, nor is it intended to suggest that similar products could not be used. All our business transactions shall exclusively be governed by our General Sales Conditions.

Sasol Germany GmbH

Anckelmannsplatz 1, 20537 Hamburg Postanschrift: Postfach 26 18 05, 20508 Hamburg
Telefon: +49 40 63 684-1000 Telefax: +49 40 63 684-3700 info@de.sasol.com www.sasol.com
Geschäftsführung: Dr. Jens Straatmann Vorsitzender des Aufsichtsrats: Christian Schindler
Sitz der Gesellschaft: Hamburg Registergericht: Amtsgericht Hamburg HRB 78475